



UniTaxitop P3.3

- 5000nit brightness adjustable, 24/7 working at softest light
- 3840Hz refresh rate, silky smooth image quality
- IP65 waterproof, get ready for harsh environment
- Play specific ADs in certain area, maximize advertising benefit
- PC or smart phone remote cluster control



Technical Specifications

Pixel Pitch	3.33mm
Pixel Configuration	SMD1921
Brightness	5000nit
Display Size WxH	960x320mm, dual sided
Display Resolution	288x96, dual sided
Unit Size WxHxD	1102x405x136mm
Horizontal Viewing Angle	+/-70°
Vertical Viewing Angle	+/-70°
Recommended Viewing Distance	3-10m
Cabinet Material	Aluminum
Cabinet Weight	15kg
Protection grade	IP65
Color Temperature	2000-9500K Adjustable
Grey Scale	14bit
Contrast Ratio	3000:1
Video Frame Rate	50/60Hz
Refresh Rate	3840Hz
Power Consumption	Max 400W, Typical 120W
Storage Temperature / Humidity	-30~+60℃, 10~95%RH
Operating Temperature / Humidity	-30~+60℃, 10~95%RH
Maintenance	Front service
Input Voltage	DC 9-36V
Input Signal	DVI/HDMI/VGA/SDI/DP/AV/S-Video
Brightness Control	Automatic
LED Lifetime	>100,000 Hours
Service	Design, Configuration, Installation, Local repair